




**Busbar support, for CI enclosure 375mm, 3x hxd=40x10mm**

**Part no.** SH1603/4  
**Catalog No.** 065366

**EL-Nummer (Norway)** 2502268

### Delivery program

			
Product range			xEnergy Safety Ci
Basic function			Prepared enclosures
Product function			Accessories for busbar enclosures
Accessories			Busbar support
Function			For use between two enclosures
Description			Component mounting possible on busbar Interval between busbar supports max. 375 mm
Interval between busbar centres		mm	50
Width		mm	375
Rated operational current	$I_e$	A	1600
For use with			L1, L2, L3: 3 x 40 x 10
For use with			C148... C145... C144...

### Technical data ETIM 8.0

Energy distribution systems (EG000015) / Busbar support (EC001166)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar support (ecl@ss10.0.1-27-40-06-07 [AC0377011])			
Number of poles			3
Max. rated current		A	1600
Busbar distance		mm	50

### Additional product information (links)

Manufacturer's Declaration CI-RoHS	<a href="https://es-assets.eaton.com/DOCUMENTATION/PDF/2013-01-31_Ci_RoHS.pdf">https://es-assets.eaton.com/DOCUMENTATION/PDF/2013-01-31_Ci_RoHS.pdf</a>
Declaration of conformity	<a href="https://es-assets.eaton.com/DOCUMENTATION/PDF/ci_ce.pdf">https://es-assets.eaton.com/DOCUMENTATION/PDF/ci_ce.pdf</a>
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&RenderModelCertification=xEnergy Safety Ci	<a href="http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;model certification xEnergy Safety Ci">http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;model certification xEnergy Safety Ci</a>
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&RenderModelCertification=xEnergy Safety Ci	<a href="http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;Save time - we assist you with expert pre-assembly">http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;Save time - we assist you with expert pre-assembly</a>
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&RenderModelCertification=xEnergy Safety Ci	<a href="http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;product information xEnergy Safety Ci">http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&amp;product information xEnergy Safety Ci</a>
tool for calculating the power loss for switching device combinations	<a href="http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/TCTool/index.htm">http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/TCTool/index.htm</a>
configurator - xEnergy family	<a href="http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/xEnergyMainSupport/index.htm">http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/xEnergyMainSupport/index.htm</a>