

Timing relay multi-function, 2 functions, 1 changeover contacts



Part no. **ZRER/W**
110405

General specifications		
Product name		Eaton Distribution parts
Part no.		ZRER/W
EAN		4015081099450
Product Length/Depth		65 millimetre
Product height		87 millimetre
Product width		17.5 millimetre
Product weight		0.067 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Ambient operating temperature - max		55 °C
Ambient operating temperature - min		-25 °C
Degree of protection		IP20
Electric connection type		Screw connection
Functions		Delay-on energization Delay on de-energization
Nominal current		8 A
Number of outputs (delayed, change-over contact)		1
Number of outputs (delayed, normally closed contact)		0
Number of outputs (delayed, normally open contact)		0
Number of outputs (undelayed, change-over contact)		0
Number of outputs (undelayed, normally closed contact)		0
Number of outputs (undelayed, normally open contact)		0
Operating voltage at AC, 50 Hz - max		240 V
Operating voltage at AC, 50 Hz - min		24 V
Operating voltage at AC, 60 Hz - max		240 V
Operating voltage at AC, 60 Hz - min		24 V
Operating voltage at DC - max		240 V
Operating voltage at DC - min		24 V
Rated control supply voltage (Us) at AC, 50 Hz - max		240 V
Rated control supply voltage (Us) at AC, 50 Hz - min		24 V
Rated control supply voltage (Us) at AC, 60 Hz - max		240 V
Rated control supply voltage (Us) at AC, 60 Hz - min		24 V
Rated control supply voltage (Us) at DC - max		240 V
Rated control supply voltage (Us) at DC - min		24 V
Starting current - max		8 A
Static heat dissipation, non-current-dependent		1.5 W
Suitable for		DIN rail (top hat rail) mounting Front mounting
Time range - max		360000 s
Time range - min		0.05 s
Voltage type		AC/DC
Voltage type of operating voltage		AC/DC

Technical data ETIM 8.0

Relays (EG000019) / Timer relay (EC001439)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Relay and socket / Timed relay (ec@ss10.0.1-27-37-16-05 [AKF092013])		
Type of electric connection		Screw connection
Function delay-on energization		Yes
Function delay on de-energization		Yes
Function floating contact on energization		No
Function floating contact on de-energization		No
Function star-delta		No
Function pulse shaping		No
Function flashing, starting with pause, fixed time		No
Function flashing, starting with pulse, fixed time		No
Clock function, starting with pause, variable		No
Clock function, starting with pulse, variable		No
With plug-in socket		No
Remote operation possible		No
Suitable as remote control		No
Pluggable on auxiliary contact block		No
Rated control supply voltage Us at AC 50HZ	V	24 - 240
Rated control supply voltage Us at AC 60HZ	V	24 - 240
Rated control supply voltage Us at DC	V	24 - 240
Voltage type for actuating		AC/DC
Nominal current	A	8
Time range	s	0.05 - 360000
Number of outputs, undelayed, normally closed contact		0
Number of outputs, undelayed, normally open contact		0
Number of outputs, undelayed, change-over contact		0
Number of outputs, delayed, normally closed contact		0
Number of outputs, delayed, normally open contact		0
Number of outputs, delayed, change-over contact		1
Outputs, reversible delayed/undelayed		No
With semiconductor output		No
Suitable for DIN rail (top hat rail) mounting		Yes
Suitable for front mounting		Yes
Width	mm	17.5
Height	mm	87
Depth	mm	65