



Thru-beam photoelectric sensor, transmitter, Sn=250m, 4L, 10-30VDC, NPN, PNP, M30, metal, line 2m

Part no. E58-30TS250-HA
Catalog No. 135696
Alternate Catalog No. E58-30TS250-HA

Delivery program

| | | | |
|--|-------|----|--|
| Basic function | | | Optical sensors |
| Product range | | | E58 Harsh Duty Series |
| For connection of: | | | 2 m connection cable |
| Design (outer dimensions) | | mm | M30 x 1.5 |
| Rated operational voltage | U_e | | 10 - 30 V DC |
| Rated switching distance | S_n | mm | 250000 |
| Description | | | Source (for combination with detector) |
| Connection | | | 4-wire |
| Function | | | Thru-beam photoelectric sensor |
| Type of light | | | Visible red |
| Material | | | Stainless steel |
| Switching type | | | NPN PNP |
| Information relevant for export to North America | | | |
| Product Standards UL 508; CSA-C22.2 No. 14; IEC60947-5-2; CE marking | | | |
| UL File No. E166051 | | | |
| UL Category Control No. NRKH, NRKH7 | | | |
| CSA File No. UL report applies to both Canada and US | | | |
| CSA Class No. – | | | |
| North America Certification UL listed, certified by UL for use in Canada | | | |
| Max. Voltage Rating 30 V DC | | | |
| Degree of Protection IEC: IP68, IP69K; UL/CSA Type: 1, 2, 3, 3R, 3S, 4, 4x, 6, 6P, 12, 12K, 13 | | | |

Technical data

General

| | | | |
|-----------------------------|--|---|----------------------------|
| Standards | | | IEC/EN 60947-5-2 |
| Ambient temperature | | | -40 - +55 |
| Mechanical shock resistance | | g | 100 Shock duration 3 ms |
| Degree of Protection | | | IP69 |

Characteristics

| | | | |
|---------------------------|-------|-----|---|
| Rated switching distance | | | |
| Rated switching distance | S_n | mm | 250000 |
| Range | | mm | 250 |
| Rated operational voltage | U_e | | 10 - 30 V DC |
| Maximum load current | I_e | mA | < 100 |
| Response time | | ms | 1.6 |
| Operating voltage display | | LED | red |
| Protective functions | | | Short-circuit protective device Protection against polarity reversal Protection against wire breakage |
| Connection | | | 4-wire |
| Style | | | |
| Design (outer dimensions) | | mm | M30 x 1.5 |
| For connection of: | | | 2 m connection cable |
| Material | | | Stainless steel |

Design verification as per IEC/EN 61439

| | | | |
|--|--|----|-----|
| Technical data for design verification | | | |
| Operating ambient temperature min. | | °C | -40 |
| Operating ambient temperature max. | | °C | 55 |

Technical data ETIM 7.0

| | | | |
|---|--|----|------------------------|
| Sensors (EG000026) / One-way light barrier (EC002716) | | | |
| Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Optoelectronic sensor / One-way light barrier (ecl@ss10.0.1-27-27-09-01 [AKP250013]) | | | |
| Scope of delivery of the one-way system | | | Transmitter |
| Opening angle | | ° | 0 |
| Pre failure notice | | | No |
| With time function | | | No |
| Rated switching distance | | mm | 250000 |
| Max. switching distance | | mm | 0 |
| Max. output current | | mA | 0 |
| Reflector included | | | No |
| Analogue output 0 V ... 10 V | | | No |
| Analogue output 0 mA ... 20 mA | | | No |
| Analogue output 4 mA ... 20 mA | | | No |
| Analogue output -10 V ... +10 V | | | No |
| With other analogue output | | | No |
| Setting procedure | | | Other |
| With communication interface analogue | | | No |
| With communication interface AS-Interface | | | No |
| With communication interface CANOpen | | | No |
| With communication interface DeviceNet | | | No |
| With communication interface Ethernet | | | No |
| With communication interface INTERBUS | | | No |
| With communication interface PROFIBUS | | | No |
| With communication interface RS-232 | | | No |
| With communication interface RS-422 | | | No |
| With communication interface RS-485 | | | No |
| With communication interface SSD | | | No |
| With communication interface SSI | | | No |
| Number of semiconductor outputs with signalling function | | | 0 |
| Number of contact energized outputs with signalling function | | | 0 |
| Number of protected semiconductor outputs | | | 0 |
| Number of protected contact energized outputs | | | 0 |
| Type of interface for safety communication | | | Other |
| Type of electric connection | | | Cable |
| Type of switching output | | | Other |
| Type of switch function | | | Other |
| Operation agent-safety class | | | Safety class 2 |
| Explosion safety category for gas | | | None |
| Explosion safety category for dust | | | None |
| Construction type housing | | | Cylinder, screw-thread |
| Width sensor | | mm | 0 |
| Diameter sensor | | mm | 30 |
| Height of sensor | | mm | 0 |
| Length of sensor | | mm | 111 |
| Sensing mode | | | Light-/dark switching |
| Material of optical surface | | | Glass |
| Material housing | | | Metal |
| Max. output current at protected output | | mA | 0 |
| Min. reflector distance | | mm | 0 |

| | | |
|---|-----------------|---------|
| Ambient temperature | °C | 40 - 55 |
| Time of reaction | ms | 1.6 |
| Transmission range of the safety field | m | 0 |
| Switching frequency | Hz | 312 |
| Type of safety acc. IEC 61496-1 | | |
| "Switching voltage of OSSD at state ""high"" | V | 30 |
| Rated control supply voltage Us at AC 50HZ | V | 0 - 0 |
| Rated control supply voltage Us at AC 60HZ | V | 0 - 0 |
| Rated control supply voltage Us at DC | V | 10 - 30 |
| Voltage type | | DC |
| With monitoring function downstream switching devices | | No |
| Laser protection class | | None |
| Wavelength of the sensor | nm | 660 |
| Type of light | | Other |
| Light dot | mm ² | 0 |
| AWG-number | | 0 |
| Material of cable sheath | | Other |
| With restart blockage | | No |
| Suitable for safety functions | | No |
| Degree of protection (IP) | | IP67 |
| Degree of protection (NEMA) | | 4X |

Approvals

| | | |
|-----------------------------|--|---|
| Product Standards | | UL 508; CSA-C22.2 No. 14; IEC60947-5-2; CE marking |
| UL File No. | | E166051 |
| UL Category Control No. | | NRKH, NRKH7 |
| CSA File No. | | UL report applies to both Canada and US |
| CSA Class No. | | - |
| North America Certification | | UL listed, certified by UL for use in Canada |
| Max. Voltage Rating | | 30 V DC |
| Degree of Protection | | IEC: IP68, IP69K; UL/CSA Type: 1, 2, 3, 3R, 3S, 4, 4x, 6, 6P, 12, 12K, 13 |

Dimensions

